



TUNDRA 450 AMP MIG WELDER (3 PHASE)

KIT-TUNMIG450S

- Supply Voltage: 3 X 400V
- Supply Frequency: 50Hz
- Max Supply Current: 33A
- Supply Power: 22.9kVA
- Slow Fuses: 25A
- Welding Range: 40-450A
- No Load Voltage: 17.5-48V
- Duty Cycle: 100% - 310A, 60% - 420A, 50% - 450A
- Voltage Steps: 30
- Welding Wire Ø: 0.8mm - 1.6mm
- Protection: IP23
- Insulation Class: H
- Cooling: AF
- Dimensions (LxBxH): 585 x 700 x 920mm
- Weight: 148kg

WF500

- Supply Voltage: 42V AC
- Supply Power: 110W
- Welding Range: up to 500A
- Welding Wire Ø: 0.8mm - 1.6mm
- Protection: IP23
- Insulation Class: H
- Motor: 42V DC
- Driven Rolls: 2/4
- Wire Speed: 1-20m/min
- Rolls Diameter: 30mm
- Dimensions: 640 x 480 x 250mm
- Weight: 18kg



FOUR ROLL
WIRE FEEDER



WF500

CASTOR WHEELS



Jefferson[®]
PROFESSIONAL TOOLS & EQUIPMENT